



## Art. -Nr. P860

- Werkzeugaufnahme für handelsübliches Zubehör
- Langlebiger leistungsstarker Motor
- Metallgetriebe für hohe Standzeit
- Mechanische Sicherheitskupplung
- Elektronik Sanftlauf
- Zuschaltbarer Softschlag

## Technische Daten

Bezeichnung	ESD 1801
Hersteller	Eibenstock
Leistungsaufnahme	1.800 W
Nennspannung	230 V ~
Nenndrehzahl	0-2.050 min <sup>-1</sup>
Leerlaufdrehzahl	0-3.000 min <sup>-1</sup>
Schlagfrequenz	41.000 Schläge/min
max Bohrdurchmesser	90 mm
Werkzeugaufnahme	M 18 aussen
Spannhalsdurchmesser	53 mm
Gewicht	5,9 kg

Verpackungseinheit	1 Stück
Set bestehend aus	Primo Schnelläufer P860 Zentrierbohrer für Absaugung P856 Absaugung P855 Diamantbohrkrone 82 mm P850 (Set Mauerwerk) oder Diamantbohrkrone softschlag 82 mm P851 (Set Kalksandstein/Beton)
	Koffer
EAN	4260182064900

## Art. -Nr. P860



- Tool holder for commercially available accessories
- Durable powerful motor
- Metal gearbox for high stability
- Mechanical safety clutch
- Electronics Soft start
- Switchable soft impact

## Technical data

Description ESD	1801
Manufacturer	Eibenstock
Power consumption	1,800 W
Nominal voltage	230 V ~
Rated speed	0-2,050 min <sup>-1</sup>
Idling speed	0-3,000 min <sup>-1</sup>
Stroke frequency 4	1,000 strokes/min
max drill diameter	90 mm
Tool holder	M 18 external
Clamping neck diameter	53 mm
Weight	5,9 kg

Packaging unit	1 piece
Set consisting of	Primo high-speed runner P860 Center drill for suction P856 Suction P855 Diamond core bit 82 mm P850 (set masonry) or Diamond core bit soft impact 82 mm P851 (set sand-lime brick/ concrete) Suitcase
EAN	4260182064900