

**Art.-Nr. P698**


- Farblich codiert
- Einfache Handhabung ohne Zusatzwerkzeug
- Geeignet für eindrätige Kupferleitungen
- 50 % weniger Platzbedarf

**Technische Daten****Sonstige Eigenschaften**

Material Gehäuse	Polycarbonat (94-V2)
Material Kontakteinsatz	Messing (verzinnt)
Feder	Edelstahl
Selbstverlöschend	Ja (nach UL94-V2)
Netzspannung	450 V
Nennstrom	24 A
EAN	4260182062234
Zolltarif-Nr.	85369010

**Abmessungen & Verpackungen**

Querschnitt	0,5 bis 2,5 mm <sup>2</sup>
Bemessungsanschlussvermögen	0,5 bis 2,5 mm <sup>2</sup>
Verpackungseinheit	100 Stück

**Order-no. P698**

- Color coded
- Easy handling without additional tools
- Suitable for single-wire copper cables
- 50% less need for space

**Technical data****Other characteristics**

Material Housing	Polycarbonate (94-V2)
Material contact insert	brass (tinned)
Spring	stainless steel
Self-extinguishing	yes (according to UL94-V2)
Mains voltage	450 V
Rated current	24 A
EAN	4260182062234
Customer tariff number	85369010

**Dimensions & packaging**

Cross-section	0.5 to 2.5 mm <sup>2</sup>
Dimension Connection Capacity	0.5 to 2.5 mm <sup>2</sup>
Packing unit	100 pieces