



Produkteigenschaften

Form	rund, mit Trafo
Tiefe	120 mm
Einbaudurchmesser	Individuell bis 300 mm
Gesamthöhe	120 mm
Gehäusedurchmesser	320 mm
Farbe	schwarz
Anzahl Rohreinleitungen	2 x M20 und 2 x M25
Zugentlastung	Nein

Betoneinbaugehäuse XL 300 - Ein betondichtetes Einbaugehäuse für Ortbeton und Werksfertigung

- » Für Ortbeton und Werksfertigung
- » Membrantechnik
- » Werkzeuglose Rohreinleitung M20/M25
- » Absolut betondicht
- » Ohne Trafotunnel
- » Mit Mineralfaserplatte

Serie	-
Artikelnummer	P606
Kategorie	Betoninstallation
Montageart	Nagel, Kleber
Einsatz	Ortbeton, Werksfertigung
EAN	4260182062180

Materialeigenschaften

Material Gehäuse	PP
Material Einführung	TPE



Product features

Shape	round with tunnel
Depth	120 mm
Installation diameter	Individual till 300 mm
Height	120 mm
Housing diameter	320 mm
Color	black
Number of conduit entries	2 x M20 and 2 x M25
Strain relief	No

XL 300 installation housing - A concrete-tight installation housing for cast-in-place concrete and prefabrication

- » For cast-in-place concrete and prefabrication
- » Membrane technology
- » Toolless conduit insertion M20/M25
- » Absolutely concrete-tight
- » Without tunnel
- » With mineral fibre board

Series	-
Article No.	P606
Category	Concrete installation
Type of installation	Nail, glue
Use	Cast-in-place concrete, prefabrication
EAN	4260182062180

Material properties

Material housing	PP
Membrane material	TPE