



Produkteigenschaften

| | |
|---------------------|---|
| Netzspannung | 450 V |
| Nennstrom | 32 A |
| Klemmstellen | 2-polig |
| Farbe | transparent, weiß |
| Leitungsquerschnitt | 0,2 mm ² , 0,5 mm ² , 1,0 mm ² , 1,5 mm ² , 2,0 mm ² , 2,5 mm ² , 4,0 mm ² |

**Verbindungsklemme mit Betätigungshebel
2-polig**

- » universell einsetzbar für feindrähtige, eindrätige und mehrdrätige Leiter
- » geeignet für Leiter mit einem Durchmesser von 0,2 bis zu 4,0 mm²
- » mit Sichtfenster für die vereinfachte Kontrolle der korrekten Leiterposition

| | |
|---------------|----------------------|
| Serie | - |
| Artikelnummer | P747 |
| Kategorie | Hohlwandinstallation |
| Montageart | - |
| Einsatz | Hohlwand |
| EAN | 4260182064375 |



Product features

| | |
|-----------------|--------------------|
| Mains voltage | 450 V |
| Rated current | 32 A |
| Clamping points | 2-pole |
| Color | transparent, white |

| | |
|--------------------|---|
| Wire cross section | 0,2 mm ² , 0,5 mm ² , 1,0 mm ² , 1,5 mm ² , 2,0 mm ² , 2,5 mm ² , 4,0 mm ² |
|--------------------|---|

Connector with operatig lever 2-pole

- » universally applicable for fine-stranded, solid and stranded conductors
- » suitable for conductors with an average of 0.2 up to 4.0 mm²
- » with viewing window for simplified control of the correct conductor position

| | |
|----------------------|--------------------------|
| Series | - |
| Article No. | P747 |
| Category | Cavity wall installation |
| Type of installation | - |
| Use | Cavity wall |
| EAN | 4260182064375 |